

Greater Vancouver Sewerage and Drainage District • Metro Vancouver Housing Corporation

4330 Kingsway, Burnaby, BC, Canada V5H 4G8 604-432-6200 www.metrovancouver.org

Metropolitan Planning, Environment and Parks Department Tel. 604-432-6200 Fax 604-436-6707

### **PERMIT GVA0460**

Pursuant to
Greater Vancouver Regional District Air Quality Management Bylaw No. 1082, 2008
and BC Environmental Management Act

### **Precision Heat Treat Ltd.**

located at #7 - 8285 132nd Street, Surrey, BC V3W 4N6

is authorized to discharge air contaminants to the air from a steel heat treating facility

subject to the requirements in this Permit for the emission sources and works existing or planned on January 19, 2012.

Contravention of any of these requirements is a violation of the bylaw and may result in enforcement action.

Issued: Amended: November 16, 1992 January 19, 2012 Don Miller Assistant District Director

Page 1 of 11

### **SECTION 1 – AUTHORIZED EMISSION SOURCES**

Authorization to discharge air contaminants from the authorized Emission Sources and Works listed below are subject to the specified terms and conditions.

Approximate locations of the emission sources are shown on the Site Plan in section 4.

### EMISSION SOURCE 01: Heat Treating (Hardening) Furnace discharging through a Stack(s).

MAXIMUM EMISSION FLOW RATE: 5 m³/min MAXIMUM ANNUAL OPERATING HOURS: 8760 hrs/yr MAXIMUM PRIMARY BURNER INPUT FIRING RATE: 0.53 GJ/hr

### MAXIMUM EMISSION QUALITY:

10% Opacity.

### **WORKS AND PROCEDURES:**

The firing of the heat treating (hardening) furnace with natural gas, using good combustion practices and operating procedures

### EMISSION SOURCE 02: Heat Treating (Hardening) Furnace discharging through a Stack(s).

MAXIMUM EMISSION FLOW RATE: 5 m³/min MAXIMUM ANNUAL OPERATING HOURS: 8760 hrs/yr MAXIMUM PRIMARY BURNER INPUT FIRING RATE: 0.53 GJ/hr

### MAXIMUM EMISSION QUALITY:

10% Opacity.

### WORKS AND PROCEDURES:

The firing of the heat treating (hardening) furnace with natural gas, using good combustion practices and operating procedures

### EMISSION SOURCE 03: Heat Treating (Hardening) Furnace discharging through a Stack(s).

MAXIMUM EMISSION FLOW RATE: 5 m³/min MAXIMUM ANNUAL OPERATING HOURS: 8760 hrs/yr MAXIMUM PRIMARY BURNER INPUT FIRING RATE: 0.21 GJ/hr

### MAXIMUM EMISSION QUALITY:

1. 10% Opacity.

Issued:

November 16, 1992

Amended:

January 19, 2012

Don Miller

**Assistant District Director** 

### WORKS AND PROCEDURES:

The firing of the heat treating (tempering) furnace with natural gas, using good combustion practices and operating procedures.

### EMISSION SOURCE 04: Inert Gas Generator discharging through a Stack(s).

MAXIMUM EMISSION FLOW RATE: 5 m<sup>3</sup>/min MAXIMUM ANNUAL OPERATING HOURS: 8760 hrs/yr MAXIMUM PRIMARY BURNER INPUT FIRING RATE: 0.42 GJ/hr

### MAXIMUM EMISSION QUALITY:

10% Opacity.

### **WORKS AND PROCEDURES:**

The firing of the inert gas generator with natural gas, using good combustion practices and operating procedures.

### EMISSION SOURCE 05: Endothermic Gas Generator discharging through a Stack(s).

MAXIMUM EMISSION FLOW RATE: **5** m³/min MAXIMUM ANNUAL OPERATING HOURS: **8760** hrs/yr MAXIMUM PRIMARY BURNER INPUT FIRING RATE: **0.26** GJ/hr

### MAXIMUM EMISSION QUALITY:

1. 10% Opacity.

### **WORKS AND PROCEDURES:**

The firing of the Can-Eng endothermic gas generator with natural gas, using good combustion practices and operating procedures.

### EMISSION SOURCE 06: Carburising Furnace discharging through a Stack(s).

MAXIMUM EMISSION FLOW RATE: 5 m<sup>3</sup>/min MAXIMUM ANNUAL OPERATING HOURS: 8760 hrs/yr MAXIMUM PRIMARY BURNER INPUT FIRING RATE: 0.42 GJ/hr

### MAXIMUM EMISSION QUALITY:

10% Opacity.

### WORKS AND PROCEDURES:

The firing of the Can Eng Model AF10 internal quench carburising furnace with natural gas, using good combustion practices and operating procedures.

Issued:

November 16, 1992

Amended:

January 19, 2012

Don Miller
Assistant District Director

### EMISSION SOURCE 07: Steel Tempering Furnace discharging through a Stack(s).

MAXIMUM EMISSION FLOW RATE: 5 m³/min
MAXIMUM ANNUAL OPERATING HOURS: 8760 hrs/yr
MAXIMUM PRIMARY BURNER INPUT FIRING RATE: 0.42 GJ/hr

### MAXIMUM EMISSION QUALITY:

1. 10% Opacity.

### WORKS AND PROCEDURES:

The firing of the Park Thermal Model 400K steel tempering furnace with natural gas, using good combustion practices and operating procedures.

Issued: Amended: November 16, 1992 January 19, 2012 Don Miller Assistant District Director

### **SECTION 2 – GENERAL REQUIREMENTS AND CONDITIONS**

### A. AMENDMENTS

The terms and conditions of this permit may be amended, as authorized by applicable legislation. New and modified sources must receive authorization prior to start-up.

### **B. POLLUTION**

Notwithstanding any conditions in this permit, no person shall discharge or allow or cause the discharge of any air contaminant so as to cause pollution as defined in the Greater Vancouver Regional District Air Quality Management Bylaw No. 1082, 2008 and the Environmental Management Act.

### C. STANDARD CONDITIONS AND DEFINITIONS

<u>Unless otherwise specified</u>, the following applies to this permit:

- Gaseous volumes are corrected to standard conditions of 20° Celsius & 101.325 kPa with zero percent moisture.
- 2. Contaminant concentrations from the combustion of specific fuel types are corrected to the following Oxygen content, unless specified otherwise:
  - 3% O<sub>2</sub> for natural gas and fuel oil;
  - 8% O<sub>2</sub> for wood fuel.
  - 15% O<sub>2</sub> for turbines
- 3. Where compliance testing is required, each contaminant concentration limit in this permit will be assessed for compliance based on a valid test using test methods approved by the District Director.
- 4. Visual opacity measurements are made at the point of maximum density, nearest the discharge point and exclude the effect of condensed, uncombined water droplets. Compliance determinations are based on a 6 minute average in accordance with the provincial "Source Testing Code for the Visual Measurement of The Opacity of Emissions from Stationary Sources". Continuous Emission Monitor System (CEMS) opacity compliance determinations are based on a one hour average (taken from the top of each hour).
- 5. If authorized in section 1 of this permit, standby fuel use is restricted to a maximum of 350 hrs/yr and to those periods during which the primary authorized fuel is not available. Fuel oil sulphur content shall not exceed 15 mg/kg and emissions during fuel oil firing shall not exceed 10% Opacity.
- 6. Definitions in the Environmental Management Act and Air Quality Management Bylaw apply to terminology used in this permit.
- 7. Threshold Limit Values (TLV) refer to the Time Weighted Average (TWA) exposure limits for substances specified in the American Conference of Governmental Industrial Hygienists Threshold Limit Values handbook, current on the latest date that this permit issuance or amendment came into effect.
- 8. Sulphur Oxides (SOx) are expressed as Sulphur Dioxide.
- 9. Nitrogen Oxides (NOx) are expressed as Nitrogen Dioxide.
- 10. The Canadian Council of Ministers of the Environment (CCME) "Environmental Guidelines for Controlling Emissions of Volatile Organic Compounds from Aboveground Storage Tanks (June

Issued:

November 16, 1992

Amended:

January 19, 2012

Don Miller Assistant District Director

- 1995, CCME-EPC-87E)" shall be adhered to for all applicable tanks unless otherwise stated in this permit.
- 11. Authorized 'Maximum Annual Operating Hours' of 8760 hrs/yr for an emission source is equivalent to authorization for continuous operation of the emission source for an entire calendar year, including leap years.

### D. HEATING, VENTILATION, AIR CONDITIONING AND INTERNAL COMBUSTION ENGINES

Air contaminants discharged from any natural gas-fired heating, ventilation or air conditioning systems for buildings and any internal combustion engines located at the discharge site shall be maintained and operated in a manner prescribed by the manufacturer to ensure good combustion of the fuel with minimum discharge of air contaminants.

### E. AUTHORIZED WORKS AND PROCEDURES

Works and procedures, which this permit authorizes to control the discharge of air contaminants, shall be employed during all operating periods of the related facilities. The permit holder shall regularly inspect and maintain all such works in good repair.

The discharge criteria described in this permit are applicable on the issued or amended date of this permit unless specified otherwise. If a date different to the issued or amended date is specified, the existing control works and procedures must be maintained in good operating condition and operated in a manner to minimize emissions.

### F. BYPASSES

The discharge of contaminants which have bypassed authorized control works during non-emergency conditions are prohibited unless approval has been obtained in writing from the District Director.

### G. EMERGENCY PROCEDURES

In the event of an emergency that prevents compliance with a requirement(s) of this permit, that requirement(s) shall be suspended for such time as the emergency continues or until otherwise directed by the District Director, provided that:

- 1. Due diligence was exercised in relation to the process, operation or event that caused the emergency and that the emergency occurred notwithstanding this exercise of due diligence; and,
- 2. The District Director is notified at the first available opportunity of the emergency and of contingency actions invoked or planned to mitigate adverse impacts and restore compliance. Notification shall be made to Metro Vancouver's 24-hour number: 604-436-6777; and,
- 3. Due diligence is exercised in shutting down related processes and/or taking action to restore compliance in the shortest possible time frame, unless specified otherwise in this permit or by written notice from the District Director.

Notwithstanding 1, 2 and 3 above, the District Director may specify contingency actions to be implemented to protect human health and the environment while authorized works and/or standard operating procedures are being restored.

Issued:

November 16, 1992

Amended:

January 19, 2012

Don Miller

**Assistant District Director** 

If an emergency situation results in a "spill" as defined in the Environmental Management Act Spill Reporting Regulation, the spill shall also be reported immediately to the Provincial Emergency Program by telephoning 1-800-663-3456.

Issued:

Amended:

November 16, 1992 January 19, 2012 Don Miller Assistant District Director

### **SECTION 3 – REPORTING REQUIREMENTS**

## A. MONITORING REQUIREMENTS AND REPORTING

Operating Procedures and the BC Ministry of Environment Field Sampling Manual, as they may be amended from time to time. Any Unless otherwise approved by the District Director prior to any sampling or analysis, all measurements shall be performed by an independent agency in accordance with Metro Vancouver Air Emissions Sampling Program Manual of Methods and Standard variance from these procedures must receive prior approval from the District Director.

Program. Notification must be given to the Metro Vancouver, Regulation & Enforcement Division (phone 604-436-6777, Fax 604-A minimum of 3 days advance notice must be given prior to taking measurements required by this Monitoring and Sampling 436-6707, email regulationenforcement@metrovancouver.org). Unless otherwise specified, sampling shall be performed under operating conditions representative of the previous 90 calendar days which are used in this permit. These submissions shall include process data relevant to the operation of the source of the emissions of operation. All field data and calculations must be submitted with monitoring results and they shall be reported in the metric units and the performance of the emission control works.

The permit holder shall conduct the following monitoring and sampling and submit electronic reports of the results to the District Director by the dates specified below using a password enabled web based application provided by Metro Vancouver.

JURCE DI	DUE DATE	FREQUENCY	REQUIREMENT	PARAMETER(S) TEST METHOD	TEST METHOD	REPORT TYPE
N/A	N/A	N/A	N/A	N/A	N/A	N/A

lssned:

Amended:

Permit GVA0460

November 16, 1992

January 19, 2012

Don Miller

Assistant District Director

Page 8 of 11

### B. INFORMATION REPORTING REQUIREMENTS

The permit holder shall submit electronic reports containing the required information to the District Director by the dates specified below using a password enabled web based application provided by Metro Vancouver.

REPORT	0	e Materials ig and Products	Fuel Use	Solvent ne Use
REQUIREMENT	Written report providing details of the total number of hours and days operated in the preceding calendar year. Detailed records are to be maintained in a written bound log or other format approved by the District Director and made available for inspection by Metro Vancouver staff for a minimum period of three years.	Written report providing details of the types and amounts of principle products produced and principal raw materials used in the preceding calendar year.	Written report detailing the types and amounts of fuel burned in the preceding calendar year.	Written report providing details of the types, amounts and end use of organic solvents and organic solvent-containing materials used in the preceding calendar year.
FREQUENCY	Yearly	Yearly	Yearly	Yearly
DUE DATE	March 31, 2012	March 31, 2012	March 31, 2012	March 31, 2012
	01, 02, 03, 04, 05, 06, 07	Facility	04, 01, 02, 03, 05, 06, 07	Facility

Issued: Amended: Permit GVA0460

November 16, 1992 January 19, 2012

Don Miller Assistant District Director

Page 9 of 11

### C. AMENDED OR ADDITIONAL REQUIREMENTS

Based on the results of the monitoring program, including the stack sampling results or any other information, the District Director may:

- 1. Amend the monitoring and reporting requirement of any of the information required by this Permit including plans, programs and
- Require additional investigations, tests, surveys or studies. ci

Amended: Issued:

Permit GVA0460

November 16, 1992 January 19, 2012


Don Miller

Assistant District Director

### **SECTION 4 - SITE PLAN**

LEGAL DESCRIPTION OF DISCHARGE SITE: Parcel Identifier: 003-891-399, Lot 56, Section 29, Township 2, New Westminster District, Plan 66606

The following site plan is not to scale and the locations of the discharge points are approximate.



Issued: Amended:

November 16, 1992 January 19, 2012

Don Miller Assistant District Director